

SiSiB® PC5861 SILANE

- 1 -

CHEMICAL NAME

Hexadecyltrimethoxysilane

CHEMICAL STRUCTURE

INTRODUCTION

SiSiB® PC5861 is a monomeric long chain alkylfunctional silane. It is a clear colorless liquid and soluble in organic solvents, not in water.

TYPICAL PHYSICAL PROPERTIES

CAS No.	16415-12-6
EINECS No.	240-464-3
Formula	C ₁₉ H ₄₂ O ₃ Si
Molecular Weight	346.62
Boiling Point	180°C[75mmHg]
Flash Point	165°C
Viscosity	7 cSt

Color and Appearance	Colorless transparent liquid
Density 25/25°C	0.88
Refractive Index	1.431 [25°C]
Monomer Content:	Min.95.0% by GC
Active Content:	99.0%

<u>APPL</u>ICATIONS

SiSiB® PC5861 has superior hydrophobicity, it can be used as a water-repellent or



Copyright© 2012 Power Chemical Corporation Ltd. SiSiB® is a registered trademark of PCC. For more knowledge regarding organosilanes, you may visit www.SiSiB.com or www.PCC.asia



SiSiB[®] PC5861 SILANE

- 2 -

surface modifier.

SiSiB® PC5861 can be used for mineral filler treatment. When treated minerals are incorporated into polymers, the long-chain alkyl functionality results in unique functional filler properties.

SiSiB® PC5861 can be used as scorch retardant in moisture crosslinked wire and cable compounds, to improve processability and shelf life. Additive loading levels of 0.5 to 1.5 wt% based on the overall compound are typically recommended.

SiSiB® PC5861 can be used for polyolefin production.

PACKING AND STORAGE

SiSiB® PC5861 is supplied in 180Kg steel drum.

In the unopened container SiSiB® PC5861 has a shelf life of one year.

Notes

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: silanes@SiSiB.com.

